

> PRINT > COPY > SCAN > FAX

TASKalfa 6052ci

COLOUR MULTIFUNCTIONAL FOR A3 FORMAT

# COLOUR HERO WITH HIGH-SPEED PRODUCTIVITY.



The combination of outstanding colour quality at high speeds and high-capacity document processing makes the new TASKalfa 6052ci a very impressive multifunctional colour device. Supported by advanced technology, productivity is further enhanced with flexible paper-handling options and fast, economical and reliable printing. And when it comes to optimising workflows, this colour multifunctional, with its range of digital functions and optional Fiery controller, puts the power firmly in your hands.

- > Up to 60/55 pages per minute A4 in b/w and colour
- > Outstanding image quality due to advanced colour technology
- > Standard print resolution of 1,200 x 1,200 dpi, 2 bit depth (equivalent of 4,800 x 1,200 dpi)
- > Advanced paper handling from A6 up to SRA3 and beyond for up to 7,150 sheets
- > Various paper feeders and productive finishing options
- > Up to 4 GB RAM, 8 GB SSD + 320 GB HDD memory and storage
- > Long-life components providing exceptional efficiency and reliability, and less waste
- > Optional Fiery Controller for highest productivity and colour quality



TASKalfa \*\*\* The TASKalfa 6052ci not only provides stunning image results at impressive speeds - it won't let you down either. This is thanks to extremely durable components that guarantee efficient and reliable operation and meet the requirements of the most demanding of offices. The TASKalfa 6052ci offers superior colour productivity and maximum flexibility with minimum impact on the environment.

# GENERAL

Technology: KYOCERA Laser Colour, HyPAS™ solution

Platform

Touch panel size: 22.8 cm (9 inch) full-colour touch panel -90° swivel mounted

Engine speed (pages per minute): Up to 55/27 ppm A4/A3 in colour, up to 60/30 A4/A3 in b/w

Resolution: 1,200 x 1,200 dpi, 2 bit depth for print quality

of 4.800 dpi equivalent x 1.200 dpi

Warm-up time from power on: Approx. 17 seconds or less Time to first page: Approx. 3.4 sec. or less in b/w; 4.4 sec. or less in colour

CPU: Freescale QorlQ T1024 (Dual Core) 1.2 GHz Memory (standard max.): 4 GB RAM, 8 GB SSD + 320 GB HDD

Standard interface: 4x USB 2.0 (Hi-Speed), USB Host 2.0, Fast Ethernet 10 BaseT/100 BaseTX/1,000 BaseT, slot for optional print server, slot for optional SD card, slot for optional Fax System

**Dimensions (W x D x H):** Main unit: 602 x 665 x 790 mm

Weight: Main unit approx. 95 kg Power source: AC 220 V ~ 240 V, 50/60 Hz Power consumption: Printing: 960 W (in colour), 960 W (in b/w)

Ready mode: 60 W Sleep mode: 1 W or less

Noise (sound pressure level ISO 7779/ISO 9296):

Printing monochrome: 54.9 dB(A) LpA Printing in colour: 54.5 dB(A) LpA Ready mode: 33.7 dB(A) LpA **Safety standards:** GS, TÜV, CE.

This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHs compatibility

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.

Input capacity:

150-sheet multipurpose tray, 52 – 300 g/m² (Banner 135 – 165 g/m²), A6R – SRA3 (320 x 450 mm), Tab paper (136 – 256 g/m²), Banner max. 320 x 1,220 mm; 2x 500-sheet universal paper cassette, 52 – 300 g/m², upper cassette A6R up to A4R, lower cassette A6R up to SRA3, Max. input capacity with options: 7,150 sheets A4 **Duplex unit:** Duplex as standard supports

A6R-SRA3 (320 x 450 mm), 64-256 g/m² **Output capacity:** Standard 500 sheets face-down, max. output capacity 4,300 sheets

# PRINT FUNCTIONS

Controller language: PRESCRIBE

Emulations: PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and

Operating systems: All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX LINUX, as well as other operating systems on request Fonts/barcodes: 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)

Print features: Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPSe SNMPv3, quick copy, proof and hold, private print, job

storage and job management functionality

Mobile printing support: KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google Cloud Print

# COPY FUNCTIONS

Max. original size: A3
Continuous copying: 1–999
Zoom range: 25–400% in 1% steps Preset magnification ratios: 5R/5E

Digital features: Scan once copy many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page func-

Exposure mode: Auto, manual: 16 steps Image adjustments: Text + photo, text, photo, map

# SCAN FUNCTIONS

Functionality: Scan to e-mail, Scan to FTP, Scan to SMB. Scan to USB Host, Scan to box, Network TWAIN, WSD scan **Scan speed:** (A4, 300 dpi with DP-7110) b/w 180 images

per minute, colour 180 images per minute
Scan resolution: 600 x 600 dpi, 400 x 400 dpi, 300 x 300
dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit)
Max. scan size: A3, Banner up to 1,900 mm with optional Document Processor

Original recognition: Text, photo, text + photo, optimised

File types: PDF (high compressive, encrypted, PDF/A), searchable PDF (option), JPEG, TIFF, XPS, OpenXPS

## **FAX FUNCTIONS (OPTIONAL)**

Compatibility: ITU-T Super G3 Modem speed: Max. 33.6 kbps

Transmission speed: Max. 3 seconds (JBIG)

Fax resolution: Normal: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 200 x 400 dpi Ultrafine: 600 x 600 dpi

Maximum original size: A3, Banner up to 1,600 mm Compression method: JBIG, MMR, MR, MH

Features: Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

# CONSUMABLES

Average continuous toner yield in accordance with 5%

TK-8515K Toner-Kit: Toner black for 30,000 pages TK-8515C, TK-8515M, TK-8515Y Toner-Kits: Toner cyan, magenta, yellow for 20,000 pages

WT-8500 Waste Toner Bottle: 40,000 sheets (in accordance with 5% coverage b/w:colour = 7:3)

**Staple cartridge: SH-10** for DF-7100, DF-7120, BF-730 SH-12 for DF-7110

Fax System 12 Internet Fax Kit (A) Scan Extension Kit (A): Scan to searchable PDF solution (embedded OCR)

Printing System 15: Fiery Controller

Printing System Interface Kit 15: Interface board for Fiery

Paper handling DP-7100 Document processor: (Reversing), 140 sheets, 35 – 160 g/m² (simplex), A6R – Banner up to 1,900 mm DP-7110 Document processor: (one-path duplex scanning) 270 sheets, 35 – 220 g/m² (simplex), 50 – 220 g/m² (duplex), ASR – Banner up to 1,900 mm PF-7100 Paper feeder: 2x 500 sheets, 52 – 300 g/m², A6R-SRA3 (320 x 450 mm), folio

**PF-7110 Paper feeder:** 2x 1,500 sheets, 52 – 300 g/m², A4,

PF-7120 A4 side Deck: 3,000 sheets, 60-300 g/m2, A4, B5

DT-730(B) Document tray
DF-7110' Document finisher + AK-7100:

Main tray: Max. 4,000 sheets A (3,000 sheets with attachment BF-730); max. 52 – 300 g/m²; max. 66R – SRA3 Sub tray: 200 sheets A4; 52 – 300 g/m²; A6R – SRA3 AK -7100: 100 sheets; 52 – 300 g/m²; A6R – SRA3 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions,

Main tray: 1,000 sheets A4, 52–300 g/m², A6R – SRA3, 3 positions stapling up to 50 sheets A4 or 30 sheets SRA3 AK - 7100: 100 sheets; 52 – 300 g/m², A6R – SRA3, "Bridge unit AK-7100 is required for the use of DF-7110 and

Max. 500 sheets; Max. 52 – 300 g/m², A6R – SRA3; Stapling up to 50 sheets at 3 positions A4 - A3 PH-7C/PH-7D Punch unit for DF-7120/DF-7110: 2-hole/4-hole/Swedish type, 60 – 300 g/m², A5R – A3 MT-730(B) Mailbox sorter for DF-7110: 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 165 g/m2 / Dins x 100 Sheets A4, 50 Sheets A3/B4, 60 – 165 BF-730 Booklet and tri-folding unit for DF-7110 Half-folding: 52 – 256 g/m², A3, B4, A4R Booklet: Max. 16 sheets (64 pages, 60 – 90 g/m²) Non-staple folding: Max. 5 sheets (60 – 90 g/m²) Tri-folding: 60 – 105 g/m², A4R Multi tri-folding: 5 sheets (60 – 90 g/m²), 3 sheets

JS-7100 Job separator:

100-sheet internal job separator, 52 – 300 g/m<sup>2</sup>, A5R – SRA3 PH-7120: Inner punch unit for DF-7100 inner finisher PH-7130: Inner punch unit for DF-7100 inner finisher/

Swedish type Keybordholder 10

Data security kit (E): In line with ISO 15408 (common criteria) with security level EAL3 NK-7100 Numeric keypad USB IC Card Reader: Card Authentication Kit (B)AC

UG-33: ThinPrint sunnort

UG-34: Emulation (IBM Proprinter/EPSON LQ-850/ Diablo 630)

Optional interface

IB-35: Direct Wi-Fi Interface
IB-50: Gigabit-Ethernet board 10 BaseT/100 BaseTX/ 1.000 BaseT IB-51: Wireless LAN Interface

laten cover (E) CB-7100W: Wooden cabinet CB-7110M: Metal cabinet



















Copivarela - Equipamentos de Escritório, Lda.

Rua Fernando Cabral 12 - A Lumiar 1750-329 Lisboa - PORTUGAL

Tel.: (+351) 21 988 50 40 Email: comercial@copivarela.pt Site: www.copivarela.pt

KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

